Appl. No.

09/868,737

Filed

: October 15, 2001

REMARKS

Claims 1-5 have been amended to correct informalities as pointed out by the Examiner. Claims 6 and 7 have been added. Support for the amendments can be found throughout the specification (e.g., Fig. 1). As described above, the figures have been amended to correct the errors in the spelling "fullerences" which should have been "fullerenes". The specification has also been amended to correct the same errors. In compliance with 37 C.F.R. §1.125(b) and (c), a substitute specification and a marked up are attached. No new matter has been added and the claims have not been narrowed. Applicant respectfully requests entry of the amendments and reconsideration of the application in view of the amendments and the following remarks.

Rejection Under 35 U.S.C. § 112

Claims 1-5 have been rejected under 35 U.S.C. § 112, second paragraph, with regard to the informalities set forth in the Office Action. Claims 1-5 have been amended in light of the Examiner's suggestions to correct the informalities, thereby obviating the rejection. Applicant respectfully requests withdrawal of the rejection.

Allowable Subject Matter

Claims 1-5 would be allowable if rewritten or amended to overcome the rejection under 35 U.S.C. 112, second paragraph, set forth in this office action and to include all of the limitations of the base claim and any intervening claims. As explained above, Claims 1-5 have been amended to correct the informalities. Accordingly, it is respectfully submitted that Claims 1-5 are allowable.

New Claims 6 and 7

Claims 6 and 7 are dependent ultimately on Claim 1. Thus, as with Claim 1, Claims 6 and 7 also are allowable.

Appl. No.

09/868,737

Filed

.

October 15, 2001

CONCLUSION

In light of the Applicant's foregoing Remarks, it is respectfully submitted that the present application is in condition for allowance. Should the Examiner have any remaining concerns which might prevent the prompt allowance of the application, the Examiner is respectfully invited to contact the undersigned at the telephone number appearing below.

Please charge any additional fees, including any fees for additional extension of time, or credit overpayment to Deposit Account No. 11-1410. A duplicate copy of this sheet is enclosed.

Respectfully submitted,

KNOBBE, MARTENS, OLSON & BEAR, LLP

Dated: September 16, 2003 By:

Katsuhiro Arai

Registration No. 43,315

Agent of Record

Customer No. 20,995

(949) 760-0404

 $H: \label{locstoskod9B.001APC.} H: \label{locstoskod9B.001APC.} H: \label{locstoskod9B.001APC.} Local H: \label{local H: local H: local H: local H: local H: local H: local H: \label{local H: local H: local H: local H: local H: local H: local H: \label{local H: local H: local H: local H: local H: local H: local H: \label{local H: local H: local H: local H: local H: local H: \label{local H: local H: local H: local H: local H: local H: \label{local H: local H: local H: local H: local H: local H: local H: \label{local H: local H: local H: local H: local H: local H: \label{local H: local H: local H: local H: local H: local H: \label{local H: local H: local H: local H: local H: \label{local H: local H: local H: local H: local H: \local H: \loc$



VERSION WITH MARKINGS TO SHOW CHANGES MADE

KOD9B.001APC

Specification

ENT RECEIVE GROUP 1700 WATER CONTAINING FULLERANCES FULLERENES AND METHOD FOR PRODUCING THE SAME

Field of the Invention

The present invention relates to water containing fullerenesfullerenesfullerenes. It relates to a method for producing water containing fullerences fullerences floating, which comprise 60 carbon atoms forming a spheroidal structure, and an apparatus for producing the same, and healthy drinking water obtained from the same.

Background of the invention

Since long ago, charcoal and carbon have been of use in various ways in various fields, and found useful particularly for deodorization and preservation from decay, etc. Carbon's effects on the human body in health and medical treatment have also been recognized. Coping with recent social trends in health consciousness, use of carbon for health-related aspects is seen in a new light. Bicho-charcoal and bamboo charcoal are sold and used for water quality improvement and cooking, and charcoal and carbon are increasingly attracting attention.

In fields of using charcoal and carbon materials, a new material called "fullerencefullerene" was discovered more than ten years ago and was recognized as the third crystallization following diamond and graphite. In 1990, German and US joint research successfully isolated fullerences fullerences from soot produced under special conditions. Since it was reported that a potassium-metal-doped fullerencefullerene film exhibited superconductivity at the critical temperature of 18K, fullerencefullerene research has accelerated at a stretch. Due to good prospects for mass production methods for isolating fullerences fullerences and physical properties exhibited by fullerences fullerences, it attracts researchers' curiosities in both basic and applied disciplines still more. If fullerence fullerence research and technological development should advance to health-related fields, a Nobel prize will be awarded for such achievements (K. Tanigaki, K. Kikuchi, Y. Ajiha, & K. Iriyama. Fullerence Fullerene. Sangyo-tosho Co. Ltd., Oct. 1992, xvii.)

Typically, a <u>fullerencefullerene</u> comprises 60 carbon atoms forming a spheroidal structure. It is a carbon molecule with a structure of a soccer-ball like pattern combining pentagons and hexagons. It is a physically and chemically stable molecule and is known to have physical properties shown in FIG. 4 (op. cit. p.16).

Synthesis of a fullerencefullerene by a chemical reaction has not been reported. As described above, producing fullerencefullerene by physical methods has become possible. A typical production method is that: graphite is vaporized by arc discharge or laser beam irradiation to generate carbon vapor, the carbon vapor is cooled down to form soot, and a fullerencefullerene is generated in soot. FullerenceFullerene obtained by these methods has a soccer-ball like structure of 60 carbon atoms forming a spheroidal structure as shown in FIG.

3. This structure is considered to form as follows: Graphite is isolated from impurities; A five-hexagon structure changes to a morning-glory-flower-shape like structure; Carbon atoms are rearranged to approach a spherical shape and changes to a soccer-ball shape, which is energy-wise a stable structure. FullerenceFullerene generated in soot is isolated and refined by dissolving it in a solution using a refining method such as a column liquid chromatography method, etc.

The soccer-ball like structure of <u>fullerencefullerene</u> has been confirmed by a C_{60} peak by a mass spectrum, crystal structure analysis by an X-ray, and a 13 C-NMR spectrum, an infrared absorption spectrum, etc.

Thus, as production and refining methods for <u>fullerencefullerene</u> have been established and its physical and chemical properties have become clear, it attracts attention as a new next-generation functionality material and its serviceable use in various fields begins developing. Technologies for using <u>fullerencefullerene</u> are being developed: for example, in the electronics field it is used as a superconductive material, a semiconductor material or a material with strong magnetism; in the physical material field as a non-linear optical material, a catalyst, etc.; in the mechanical material field, as micro lubricant, a buffer agent, etc. Furthermore, use of <u>fullerencefullerene</u> for bioactive materials, food materials or medicines is also being proposed.

Additionally, although its details are not clear, it is reported that development of a new structural material including metal atoms such as K or La inside a spheroidal structure also attracted interests.

It is usual that a number of patent applications are reported as a new material technology develops. Fullerenee is no exception to this rule. A wide range of patent information from improvement of methods for producing and refining fullerenee fullerene to using it in the electronics, physical material or mechanical material fields has been laid open. Almost no patent journal information on use of fullerenee fullerene for bioactive materials, food materials or medicines has been laid open. If seeing a few technologies laid open until now in these fields, technologies which have been reported include: method for preserving the high degree of freshness and quality by infiltrating an ultrafine particle carbon composition solution containing fullereneesfullerenes into food such as grain reported in the Japanese Patent Laid-open No.10-45408 journal, method for inactivating a virus by oxygen in a singlet state where fullereneesfullerenes are activated and by applying rays reported in the Japanese Patent Laid-open No.9-322767 journal, cosmetic for sunburn care containing fullereneesfullerenes dissolved in its oil ingredient, whose color is inconspicuous when applied and which is excellent in sunburn protection reported in the Japanese Patent Laid-open No.9-278825 journal, etc.

Application of <u>fullerencefullerene</u> to bioactive materials, food materials or medicines is extremely important as technological development directly related to daily life and the scope of use is expected to expand. In the medical field, research on <u>fullerencefullerene</u> as a substance to enhance immunity effects of a living body is being conducted for cancer treatment purpose, etc. For example, if <u>fullerencefullerene</u> with fixed molecular weight is given to a leukocyte, production of an immune substance is stimulated. Because <u>fullerencefullerene</u> is made of carbon in its entirety, its destruction speed in the body system is remarkably slow, which makes it possible to be absorbed into the intestinal tract in the unit of nm, which is different in size from regular charcoal.

The invention laid open

As described above, expansion of <u>fullerencefullerene</u>'s application to bioactive materials, food materials or medicines is greatly hoped for. The present invention aims to solve the above-mentioned problem with the object of making the best use of this apparently unlimited serviceability of <u>fullerencefullerene</u> particularly in the fields of bioactive materials, food materials or medicines.

Having come to discover that using water containing <u>fullerencesfullerenes</u> for drinking can improve the condition of health, for example, improving bioactive functions, the inventors of the present invention completed the present invention.

A problem to be solved by the present invention is to provide a method for efficiently producing water containing <u>fullerencesfullerenes</u>, which contributes to improvement of health conditions, and an apparatus for producing the same.

In other words, the present invention aims to contribute to technological development of <u>fullerencefullerene</u> and expansion of its applications by solving the above-mentioned problem. It has developed a new method for producing water containing <u>fullerencesfullerenes</u> and an apparatus for producing the same, and healthy drinking water utilizing the newly developed water containing <u>fullerencesfullerenes</u>.

In the present invention, water containing <u>fullerencesfullerenes</u> which include water molecules is referred to as "water containing <u>fullerencesfullerenes</u>".

Fundamental characteristics of the present invention are to generate fullerences fullerences which include water molecules and drinking water in which fullerences fullerences are floating by producing fullerences fullerences in high-pressure water. Specifically, the characteristics of the present invention are listed in (1) to (4) below.

A method for producing water containing <u>fullerencesfullerenes</u>, which include water molecules and are floating in water, by burning a mixed gas of oxygen and hydrogen in high-pressure water and burning a graphite bar with a combustion gas generated.

An apparatus for producing water containing <u>fullerencesfullerenes</u>, which include water molecules and are floating in water. The apparatus possesses a tank holding high-pressure water, a jet nozzle for a mixed gas of oxygen and hydrogen, a graphite bar, an ignition system and a combustion chamber.

The apparatus for producing water containing <u>fullerencesfullerenes</u> described in (2) above, which is characterized in that a mixed gas fuel of oxygen and hydrogen is provided by electrolyzing water.

Healthy drinking water obtained by purifying water containing fullerences fullerences, which include water molecules and are floating in water.

The most important characteristic of the present invention is based on new knowledge that, unlike water containing <u>fullerencesfullerenes</u> in which <u>fullerencesfullerenes</u> simply are

floating, the water containing <u>fullerencesfullerenes</u> according to the present invention, in which <u>fullerencesfullerenes</u> including water molecules are floating in water, and these water molecules included correlatively act with a <u>fullerencefullerene</u> structure to achieve a new and remarkable bioactive action.

In response to recent social trends in health consciousness, healthy drinking water produced according to the present invention by purifying water containing fullerences fullerences, which include water molecules and are floating in water, is expected to become an epoch-making beverage sufficiently addressing requests for improvement of health. Although the reasons why fullerences fullerences which include water molecules are efficacious to health and what kind of bioactive actions they possess are unknown at present, the present invention and others are diligently conducting research to clarify the mechanisms of fullerence fullerence efficacies.

Brief description of the figure

- FIG. 1: A flow chart of producing water containing <u>fullerencesfullerenes</u> according to the present invention
- FIG 2: A schematic sketch of an apparatus for producing water containing fullerences fullerences according to the present invention
- FIG 3: A crystal structure sketch of water containing <u>fullerencesfullerenes</u> which include water molecules according to the present invention
 - FIG 4: Reported physical properties of fullerence fullerene

The best mode for carrying out the invention

As described above, methods for producing <u>fullerencefullerene</u> itself according to an industrial production scale have been established. Among them, a typical production method is that graphite of an electrode is vaporized by arc discharge or laser beam irradiation to generate carbon vapor, the carbon vapor is cooled down to form soot, and <u>fullerencesfullereness</u> are generated in soot. <u>FullerenceFullerene</u> molecules including metal atoms such as K and La are also produced by vaporizing graphite by arc discharge or laser beam irradiation. The present invention, however, does not relate to a method for producing <u>fullerencefullerene</u> itself, but it is characterized in that it relates to production of water containing <u>fullerencesfullereness</u> which include water molecules.

Water containing <u>fullerencesfullerenes</u> which include water molecules, which is obtained by the present invention, is a new product which has not been produced up to this time. The present invention does not use vaporization techniques using arc discharge or laser beam irradiation, which are conventionally known. It discloses a new method for producing water containing <u>fullerencesfullerenes</u> using a combustion method.

After diligent examination in consideration of producing water containing fullerences fullerences efficiently and economically and serving it for drinking, the inventors of the present invention came up with an idea on a method in which hydrogen and oxygen are burned, a pure graphite bar is inserted and heated in a combustion gas generated, and they were able to produce water containing fullerences fullerenes by burning hydrogen and oxygen in high-pressure water so that no substances other than water and carbon were not produced by burning hydrogen and oxygen in water.

Because the amount of <u>fullerencesfullerenes</u> contained in water containing <u>fullerencesfullerenes</u>, which is obtained by the present invention, is very small and is beyond analysis limits, it cannot be identified easily, but it can be confirmed by precision analysis. Not all carbon constitutes generated in water by the above-mentioned method are <u>fullerencesfullerenes</u>. Unburned carbon is also included. Because there is a limit for the amount of unburned carbon to be taken for drinking, it is necessary to control reaction time and the amount of fuel to be burned. If the reaction time is short, water produced does not have specific effects. If the reaction time is too long, water tastes bitter and is not suitable for drinking.

As described above, the present invention has newly developed a method for producing water containing <u>fullerencesfullerenes</u>, which include water molecules and are floating in water being processed, and an apparatus for producing the same.

Referring to figures, a method and an apparatus according to the present invention are described in detail in the following:

FIG. 1 is a flow chart of producing water containing <u>fullerencesfullerenes</u> according to the present invention. FIG. 2 is a pressure-resistant container for producing water containing <u>fullerencesfullerenes</u> according to the invention. FIG. 3 is a crystal structure of water containing <u>fullerencesfullerenes</u> obtained by the invention. FIG. 4 shows physical properties of <u>fullerencefullerene</u> itself.

An apparatus 1 for producing water containing <u>fullerencesfullerenes</u> according to the invention comprises a pressure-resistant container 2 for producing water containing <u>fullerencesfullerenes</u>, a water electrolyzer 3 for generating raw material gases and a filtration device 4 for water containing <u>fullerencesfullerenes</u>.

The basic structure of the pressure-resistant container 2 according to the invention is an apparatus for producing water containing <u>fullerencesfullerenes</u>, which include water molecules and are floating in water, comprising a tank 5 holding high-pressure water, a jet nozzle 14 for a mixed gas of oxygen and hydrogen, a combustion chamber 6 and a graphite bar 10. To this apparatus, a water electrolyzer 3 to supply raw material gasses, hydrogen and oxygen, and a filtration device 4 for water containing <u>fullerencesfullerenes</u> obtained are attached.

The pressure-resistant container 2 according to the invention comprises a metal tank, preferably a steel tank 5 holding high-pressure water. In the tank 5 holding high-pressure water, a mixed gas of oxygen and hydrogen, which are generated by the water electrolyzer 3 and are supplied from a hydrogen gas supply path 16 and an oxygen supply path 17, are blown out at high pressure from the jet nozzle 14 into the combustion chamber 6. Inside the combustion chamber 4, a graphite bar 10 is gradually pushed out from a supply cylinder 13 according to the combustion amount. A mixed gas of hydrogen and oxygen is ignited by an ignition system 11 and carbon or fullerencesfullerenes containing water molecules are discharged in pressurized water 9. The high-pressure water 9 containing these is taken out from an outlet 8 at the bottom of the tank holding high-pressure water and properly is filtrated by the filtration device 4.

Of the above-mentioned, in place of the water electrolyzer 3 for generating raw material gases, high-pressure hydrogen and oxygen gas cylinders can be used. There is, however, an advantage of using the water electrolyzer as used in the present invention over using high-pressure hydrogen gas and oxygen gas cylinders, i.e., oxygen and hydrogen supplied by water electrolysis are completely pure gases, hence raw material gases used as fuel gases can be supplied efficiently.

In the present invention, in an example of generating hydrogen 16 and oxygen 17 by water electrolysis conducted in the water electrolyzer 3 for generating raw material gases for producing water, 18, 18' and 19 respectively show cathode plates and an anode plate. As

described above, it is possible to supply hydrogen and oxygen inside the tank holding high-pressure water directly from each high-pressure hydrogen and oxygen gas cylinder.

In this apparatus, a mixed gas is perfectly burned by jetting out hydrogen 16 and oxygen 17 generated by electrolysis into the combustion chamber from the nozzle 14 through the pump, achieving a perfect vapor-gas combustion state at a very high temperature. A pure graphite bar 10 is inserted in this combustion gas, heated and burned. The graphite bar is supplied from inside the cylinder 13 by specific amount according to the amount burned. During the combustion, it is necessary to control a mixing ratio of hydrogen 16 to oxygen 17 to be strictly 2:1. It is also necessary to control a pressure inside the tank holding high-pressure water by providing a pressure control valve.

When carbon 12 heated and burned at a high temperature inside the combustion chamber 6 is discharged from the combustion chamber 4 into the high-pressure water 9, a part of carbon forms a crystal structure. This crystal structure is considered to be a morning-glory-flower-shape like carbon structure consisting of five hexagon structures called "corannulene". Carbon atoms, then, are rearranged, changing to a nearly spherical shape. At this time, one water molecule is taken in and fullerencefullerene having a cage structure larger than the water molecule contains the water molecule, changing to a soccer-ball shape, which is energy-wise a stable structure.

Main <u>fullerences fullerences</u> generated by combustion of the graphite bar are of the C_{60} structure. As described above, <u>fullerence fullerene</u> having a cage structure larger than a water molecule contains a water molecule. As shown in FIG. 3 as a type sketch, this structure is a state in which a water molecule, which is indicated as a circular dotted line, is contained in a soccer-ball-shaped structure.

As the result that a <u>fullerencefullerene</u> structure in this state is generated, it is estimated that stable carbon molecules with exceedingly high hydrophobicity are floating in water, and without using an activating agent, an apparent dissolution state is achieved.

For example, on a production scale of producing one ton of water containing fullerences fullerences, jetting a mixed gas in an injection quantity of approximately 5L/sec. for approximately two hours is appropriate. If gas pressure applied is excessive, there is a risk of destroying the structure of the apparatus. If gas pressure applied is not sufficient, gas is blown up from the combustion chamber, carbon heated is emitted on the water as it is

being covered by a bubble. This worsens generation of <u>fullerencesfullerenes</u>. A preferable air pressure at this time is approximately 3.5 atmospheres. A pressure of high-pressure water inside the tank holding high-pressure water is set to two atmospheres.

The apparatus is operated in the following manner: High-pressure hydrogen gas 16 and oxygen 17 are jetted from the nozzle 14 through the pump inside the tank holding high-pressure water and are ignited by an ignition system 11, creating a vapor-gas combustion state at a very high temperature. The pure graphite bar 10 is inserted in the combustion gas and is burned.

Further, in this apparatus, not to produce substances other than water and carbon or fullerencesfullerenes, it makes it requisite to burn hydrogen and oxygen in water. At this time, to burn hydrogen and oxygen purely in water without containing impurities, it is necessary to burn them under high pressure. The position to insert a graphite bar should be within a sphere where a mixed gas is burned perfectly and is vaporized at a completely high temperature. Because fullerencesfullerenes containing water molecules, which are generated, are carbon molecules with exceedingly high hydrophobicity, they float in water in a stable state and an apparent dissolution state is achieved without using an activating agent. New water containing fullerencesfullerenes produced in this way is taken out from the outlet and is fed to the filtration system appropriately.

Another characteristic of the present invention is to produce healthy drinking water by purifying water containing <u>fullerencesfullerenes</u>, which include water molecules and are floating in water, which was produced as described above. Because a large quantity of unburned carbon is floating in the water generated and it is not suitable for drinking as it is, water needs to be purified using a filtration system.

For a filtration method in this case, not to remove carbon or <u>fullerencesfullereness</u> generated more than necessary, using a filtration system for producing water suitable for drinking is preferable without using methods such as ion exchange and a reverse osmosis film methods, etc. In other words, a hollow fiber film is preferable as a filter. Filtrating high-pressure water drawn off from the tank holding high-pressure water using a hollow fiber film is preferable from points of view of characteristics of water containing <u>fullerencesfullereness</u> and of filter life. By doing this way, drinking water conforms to the Food Hygiene Act can be produced.

Because <u>fullerences fullerenes</u> generated are on a scale of nanomicron, it is difficult to be filtrated using a regular filter. A very small quantity of <u>fullerences fullerenes</u> is contained in high-pressure water obtained according to the present invention.

Modes for carrying out the present invention is specifically described below based on embodiments, modes for carrying out the present invention, however, are not limited to these.

Modes for carrying the invention

FIG. 2 shows a typical embodiment of an apparatus for producing water containing fullerences fullerences, which include water molecules and are floating in water, according to the present invention. The apparatus comprises a tank 5 holding high-pressure water, a jet nozzle 14 for a mixed gas of oxygen and hydrogen and a graphite bar 10.

The tank 5 holding high-pressure water is a pressure-resistant metal tank which is tolerant to ultrahigh pressure. A mixed gas of oxygen and hydrogen supplied from a hydrogen gas supply path 16 and an oxygen supply path 17 is jetted out into a combustion chamber 6 using a jet nozzle 14. A graphite bar 10 is provided inside the combustion chamber from a cylinder 13. It is necessary to control pressure inside the tank holding high-pressure water by a pressure control valve 7. A mixed gas is ignited by an ignition system 11 and fullerencesfullerenes 12 which include carbon or water molecules are discharged in the high-pressure water. Water containing fullerencesfullerenes, which include water molecules and are floating in water, is taken out from an outlet 8. The water containing fullerencesfullerenes taken out is appropriately filtrated by the filtration device 4 (comprising 21~24) and becomes a finished product.

This apparatus is operated in the following manner: As described above, by jetting a mixed gas inside a pressurized tank from the nozzle 14 by supplying hydrogen and oxygen under high pressure, igniting it by an ignition system 11, and perfectly burning it, a vapor-gas combustion state at a very high temperature is achieved. A pure graphite bar 10 is inserted in the combustion gas and is burned. When carbon heated at a high temperature inside the nozzle is discharged into high-pressure water, a part of the carbon forms a crystal structure. Carbon atoms, then, are rearranged, changing to a nearly spherical shape. At this time, a water molecule is taken in and contained. The shape changes to an energy-wise stable soccerball shape. Because fullerencefullerene containing a water molecule is a carbon molecule

with exceedingly high hydrophobicity, it floats in water in a stable state, and without using an activating agent, an apparent dissolution state is achieved.

Thus produced new water containing fullerences fullerences is taken out from an outlet and is fed to a filtration system 4. The filtration system uses hollow fiber films. Passing through hollow fiber films of 50 μ , 25 μ , 3 μ , 0.5 μ , and 0.1 μ in order, water containing fullerences fullerences with a very small quantity of fullerences fullerences is ultimately obtained.

Conditions for carrying out the invention

Internal pressure of a production tank: 2 atm.

Mixed gas: 5 liters/sec. (3.5 atm.)

Jet time: 2 hrs.

Graphite supplied: 1.5 kg/2 hrs.

Produced water containing fullerences fullerences: approx. 1 ton

By filtrating produced water containing fullerences fullerences using hollow fiber films of 50 μ , 25 μ , 3 μ , 0.5 μ , and 0.1 μ in order, healthy drinking water containing fullerencesfullerenes, which include water molecules and are floating in water.

Sampling of the healthy drinking water

52 adults consisting of men and women sampled healthy drinking water containing fullerences fullerenes, which include water molecules and are floating in water, to confirm efficacies and effects toward improving health and bioactive functions.

Sampling conditions and results

Sampling amount per day: Up to one glass 5 persons

Up to 3 glasses

22

4 glasses or more 22

Taste: Tasted nice 39

> No taste 13

Smell: Do not mind 51

Do mind

1

Efficacy examples: Physical conditions improved 22

> Appetite improved 32

Supplementary effect on medicinal action 11

Constipation relieved 14 Recovering from fatigue 49 Blood sugar level lowered 3 Diarrhea improved Better digestive functions 17 Rough skin recovered 8 Stiff shoulders relieved 18 Eyestrain recovered Gout relieved 1 Blood pressure lowered 5 Renal calculus relieved 1 Progress of lung cancer stopped 1

Progress of lung cancer stopped 1

According to the above-mentioned results, at the sampling stage, the number of people who replied "Tasted nice" was nine times more than the number of people who replied "No taste". As for its smell, nearly all respondents replied "Do not mind". From these results, it can be seen that the water containing <u>fullerencesfullerenes</u> obtained according to the present invention is a beverage which is easy to drink for many people.

Seeing from there were many people who sampled the water containing fullerences fullerences obtained according to the present invention listed effects on health-related improvements such as recovering from fatigue, appetite improved, physical conditions improved, better digestive functions, stiff shoulders relieved, constipation relieved, etc., the water containing fullerences fullerences obtained according to the present invention is considered to exhibit sufficient effects as a healthy beverage.

Industrial applicability

The present invention provides a method and an apparatus for producing new water containing <u>fullerencesfullerenes</u>, and healthy drinking water utilizing the new water containing <u>fullerencesfullerenes</u>. With the invention, <u>fullerencesfullerenes</u> can be produced in a simplified and efficient manner. Seeing from the sampling test conducted with many monitors, water containing <u>fullerencesfullerenes</u>, which include water molecules and are floating in water, is remarkably effective as a healthy beverage.

Expectations are also placed on use of water containing <u>fullerencesfullerenes</u> according to the present invention for improving the body's immune system in addition to its health improvement actions.

Abstract

A method and an apparatus for producing healthy drinking water containing fullerences fullerences, which is excellent as healthy water, are provided. In high-pressure water, by burning a mixed gas of oxygen and hydrogen and burning carbon using the combustion gas generated, water containing fullerences fullerences, which include water molecules and are floating in water, is produced. The water containing fullerences fullerences obtained is useful as healthy drinking water.

H:\DOCS\KOA\KOD9B.001APC.sub-spec.DOC 091203